

**AVAILABLE  
WITHIN  
1-2 WEEKS**  
EX WORKS  
VAHLE KAMEN



**SPRING OPERATED CABLE REELS  
FAST DELIVERY PROGRAM**



# FAST DELIVERY PROGRAM

## AT A GLANCE

- Available within 1-2 weeks ex works VAHLE Kamen
- Cable reel complete with accessories
- Slipping body with 1.5 m cable as standard
- Delivery with cable on request
- Cost-effective
- For an individual layout, please contact us

SPRING OPERATED CABLE REEL			
Reel Type	Coiling length in Meter		Article No.
	Horizontal	Vertical	
<b>4x1,5 mm<sup>2</sup>, Ø 11,2 mm, 0,16 kg/m</b>			
VLF 155-1-908-4-26	7	7	902010
VLF 180-1-931-4-26	12	12	902020
VLF 180-2-931H-4-26	27	18	902022
VLF 220-2-951H-4-26	26	26	902102
VLF 300-2-952H-4-26	47	35	902291
<b>5 x 1,5 mm<sup>2</sup>, Ø 11,8 mm, 0,18 kg/m</b>			
VLF 155-1-908-5-26	7	7	902016
VLF 180-1-931-5-26	12	12	902040
VLF 180-2-931H-5-26	20	18	902042
VLF 220-2-951H-5-26	26	25	902132
VLF 300-2-952H-5-26	47	31	902322
<b>7 x 1,5 mm<sup>2</sup>, Ø 13,3 mm, 0,23 kg/m</b>			
VLF 155-1-908-7-26	7	7	902008
VLF 180-1-931-7-26	10	10	902043
VLF 220-1-951-7-26	12	12	902160
VLF 220-2-951H-7-26	20	20	902116
VLF 221-2-951H-7-26	26	24	902282
VLF 300-2-972H-7-26	35	34	902295
VLF 300-2-952H-7-26	49	24	902352
<b>12 x 1,5 mm<sup>2</sup>, Ø 16,9 mm, 0,36 kg/m</b>			
VLF 180-1-931-12-26	7	7	902058
VLF 220-1-951-12-26	12	12	902183
VLF 220-2-951H-12-26	22	15	901364
VLF 221-2-951H-12-26	29	15	902283
VLF 300-2-952-12-26	22	22	902371
VLF 300-2-952H-12-26	50	15	902372
<b>18 x 1,5 mm<sup>2</sup>, Ø 17,9 mm, 0,47 kg/m</b>			
VLF 220-1-951-18-26	8	8	902115
VLF 221-2-951H-18-26	18	12	902281
VLF 300-2-952-18-26	23	23	902377
VLF 300-2-972H-18-26	29	21	901435
VLF 420-1-953-18-36	40	14	901436
VLF 420-2-983H-18-36	73	14	902509


SPRING OPERATED CABLE REEL			
Reel Type	Coiling length in Meter		Article No.
	Horizontal	Vertical	
<b>24 x 1,5 mm<sup>2</sup>, Ø 22,6 mm, 0,59 kg/m</b>			
VLF 300-2-952-24-36	24	19	902380
VLF 420-2-953-24-36	41	22	902520
<b>30 x 1,5 mm<sup>2</sup>, Ø 24,2 mm, 0,71 kg/m</b>			
VLF 300-2-952-30-36	20	16	900316
VLF 420-2-953-30-36	38	20	901437
<b>4 x 2,5 mm<sup>2</sup>, Ø 12,1 mm, 0,21 kg/m</b>			
VLF 155-1-908-4-26	7	7	902010
VLF 180-1-931-4-26	10	10	902020
VLF 180-2-931H-4-26	18	16	902022
VLF 220-2-951H-4-26	26	26	902102
VLF 300-2-952H-4-26	46	27	902291
<b>5 x 2,5 mm<sup>2</sup>, Ø 12,8 mm, 0,24 kg/m</b>			
VLF 155-1-908-5-26	7	7	902016
VLF 180-1-931-5-26	11	11	902040
VLF 180-2-931H-5-26	18	14	902042
VLF 220-2-951H-5-26	26	23	902132
VLF 300-2-952H-5-26	46	23	902322
<b>7 x 2,5 mm<sup>2</sup>, Ø 14 mm, 0,31 kg/m</b>			
VLF 180-1-931-7-26	10	10	902043
VLF 220-1-951-7-26	12	12	902160
VLF 220-2-951H-7-26	17	17	902116
VLF 221-2-951H-7-26	26	18	902282
VLF 300-2-952H-7-26	47	18	902352
VLF 300-2-972H-7-26	36	30	902295
<b>12 x 2,5 mm<sup>2</sup>, Ø 20,2 mm, 0,48 kg/m</b>			
VLF 220-1-951-12-26	10	10	902183
VLF 221-2-951H-12-26	16	12	902283
VLF 300-2-952-12-26	25	23	902371
VLF 420-1-953-12-36	41	15	902500




### SPRING OPERATED CABLE REEL

Reel Type	Coiling length in Meter		Article No.
	Horizontal	Vertical	
<b>18 x 2,5 mm<sup>2</sup>, Ø 20,6 mm, 0,68 kg/m</b>			
VLF 220-1-951-18-26	8	8	902115
VLF 221-2-951H-18-26	15	8	902281
VLF 300-2-952H-18-26	26	8	901428
<b>24 x 2,5 mm<sup>2</sup>, Ø 25,5 mm, 0,82 kg/m</b>			
VLF 300-1-972-24-36	12	11	901438
VLF 300-2-972-24-36	22	22	902294
<b>30 x 2,5 mm<sup>2</sup>, Ø 28,7 mm, 0,97 kg/m</b>			
VLF 420-1-983-30-36	8	7	902525
<b>4 x 4 mm<sup>2</sup>, Ø 13,4 mm, 0,28 kg/m</b>			
VLF 180-1-931-4-40	10	10	901102
VLF 220-1-951-4-40	12	12	902110
VLF 221-2-951H-4-40	26	20	902214
VLF 300-2-952H-4-40	47	22	902302
VLF 300-2-972H-4-40	35	34	901315
<b>4 x 6 mm<sup>2</sup>, Ø 14,8 mm, 0,37 kg/m</b>			
VLF 220-1-951-4-60	12	12	902120
VLF 220-2-951H-4-60	21	15	902107
VLF 221-2-951H-4-60	26	15	901439
VLF 300-2-952H-4-60	50	15	902312
VLF 300-2-972H-4-60	36	25	901309
VLF 420-2-983H-4-60	69	18	902425
<b>4 x 10 mm<sup>2</sup>, Ø 18,8 mm, 0,61 kg/m</b>			
VLF 220-1-951-4-60	7	7	902120
VLF 220-2-951-4-60	13	13	902123
VLF 221-2-951H-4-60	20	9	901439
VLF 300-2-972H-4-60	29	15	901309
VLF 420-2-953-4-60	40	24	902421
<b>4 x 16 mm<sup>2</sup>, Ø 23,4 mm, 0,92 kg/m</b>			
VLF 300-1-952-4-125	14	6	901443
VLF 300-2-952-4-125	20	12	901122
VLF 300-2-972-4-125	18	18	901267
VLF 420-2-983-4-150	25	14	902430

### ACCESSORIES

Reel Type	Ratchet Device	Cable guide arm
		
Reel Type	Article No.	Article No.
VLF 155	901720	902062
VLF 180	901721	902063
VLF 220	901722	902064
VLF 300	901723	902066
VLF420	901724	902067

### CABLE GRIP

		
Type	Cable diameter	Article No.
VLZK12	9 - 12 mm	900393
VLZK15	12 - 15 mm	900394
VLZK20	15 - 20 mm	900395
VLZK25	20 - 25 mm	900396
VLZK30	25 - 30 mm	900397



**Paul Vahle GmbH & Co. KG**

Westicker Str. 52  
59174 Kamen  
Germany

Tel.: +49 2307 704-0  
Fax: +49 2307 704-444  
info@vahle.de

[www.vahle.com](http://www.vahle.com)